


INTEGRAL UPRIGHT CURB SECTION



INTEGRAL LIP-TYPE CURB SECTION

NOTES:

1. ALL P.C. CONCRETE SHALL BE 28-DAY 4,000 PSI STRENGTH.
2. SEE "SAW CUT AND CONSTRUCTION JOINT" STANDARDS FOR DETAIL.
3. 32' STREET WITH PARKING ONE SIDE SHALL HAVE SIDEWALK ON ONE SIDE ONLY, ALL OTHERS SHALL HAVE SIDEWALKS ON BOTH SIDES.

DRAWING NO. 301	<b>CITY OF JACKSON, MISSOURI</b>								
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black;">K.A.P. Approved</td> <td style="width: 50%; border-bottom: 1px solid black;">03/31/11 Date</td> </tr> <tr> <td colspan="2" style="border-bottom: 1px solid black;">Revisions</td> </tr> <tr> <td colspan="2" style="border-bottom: 1px solid black;"> </td> </tr> <tr> <td colspan="2"> </td> </tr> </table>	K.A.P. Approved	03/31/11 Date	Revisions						<b>PORTLAND CEMENT CONCRETE STREET STANDARD (RESIDENTIAL-LOCAL)</b>
K.A.P. Approved	03/31/11 Date								
Revisions									