


INTEGRAL UPRIGHT CURB SECTION  
AT 2% CROSS SLOPE

STANDARD



INTEGRAL UPRIGHT CURB SECTION  
AT 6% CROSS SLOPE

AS REQUIRED BY ENGINEER

NOTES:

1. ALL P.C. CONCRETE SHALL BE 28-DAY 4,000 PSI STRENGTH.
2. SEE "SAW CUT AND CONSTRUCTION JOINT" STANDARDS FOR DETAIL.

DRAWING NO. 302	<b>CITY OF JACKSON, MISSOURI</b>										
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black;">K.A.P.</td> <td style="width: 50%; border-bottom: 1px solid black;">03/31/11</td> </tr> <tr> <td style="font-size: small;">Approved</td> <td style="font-size: small;">Date</td> </tr> <tr> <td colspan="2" style="border-bottom: 1px solid black;">Revisions</td> </tr> <tr> <td colspan="2" style="border-bottom: 1px solid black;"> </td> </tr> <tr> <td colspan="2"> </td> </tr> </table>	K.A.P.	03/31/11	Approved	Date	Revisions						<b>PORTLAND CEMENT CONCRETE STREET STANDARD (COLLECTOR)</b>
K.A.P.	03/31/11										
Approved	Date										
Revisions											